January 20, 2015



TABLE OF CONTENTS

THE AGREEMEN	page no. VT1
	BOND(added to contract after bid)2 & 3
	D(added to contract after bid)4 & 5
	6
	AFETY QUALIFICATION STATEMENT7 - 8
	VT9
	NTRACTORS
	SIONS
	ATERIALS INVENTORY
	THORIZATION FORM
STANDARD DET	'AIL SHEETS
DIVISION NO. 1	GENERAL REQUIREMENTS AND COVENANTS
DIVISION NO. 2	EARTHWORK 2.08 Roadway Earthwork 2.11 Subbase 2.13 Soil Erosion and Sedimentation Control 2.16 Fine Grading
DIVISION NO. 3	BASE COURSES 3.01 Aggregate Base Course
DIVISION NO. 4	SURFACE COURSES AND PAVEMENTS 4.00 Plant-Mixed Bituminous Base, Leveling and Top Courses
DIVISION NO. 6	MISCELLANEOUS CONSTRUCTION 6.09 Concrete Curb & Gutter 6.11 Concrete Sidewalks, Ramps and Driveways 6.31 Roadway Maintenance and Traffic Control 6.53 Outlawn
DIVISION NO. 7	MIXTURES 7.01 Portland Cement Concrete
DIVISION NO. 8	STORM AND SANITARY SEWERS 8.08 Manholes, Catch Basins and Inlets 8.09 Rebuilding and Regrading Manholes 8.10 Regrading Catch Basins and Inlets

2015 ST. MARYS & VALORIE STREET RECONSTRUCTION

CONTRACT NO. 2

THE AGREEMENT

		•	A.D., 2015 by and
	hereinafte		CTOR" and the CITY OF
MIDLAND, N	MICHIGAN hereinafter call	ed the "OWNER".	
		he Owner, for the cons	ideration hereinafter named,
agree as follow	ws:		
1.	the Specifications and as r ST. MARYS & VALORIE NO. 2" The Contract Doc	the work shown on the equired by the Contract STREET RECONST uments hereby defined	e drawings and described in t Documents entitled "2015
2.		with the attached Spec	or for his work upon ifications and at the unit prices hare hereby made part of this
IN WI above written	<u> </u>	rties set their hands an	d seals the day and year first
WITNESSES		CITY OF MIDLA	AND
		BY:	
			Maureen Donker, Mayor
		BY:	
			Selina Tisdale, City Clerk
		CONTRACTOR	
		BY:	
		ADDRESS:	
		<u></u>	

2015 ST. MARYS & VALORIE STREET RECONSTRUCTION

CONTRACT NO. 2

CITY OF MIDLAND, MICHIGAN

PROPOSAL

TO: THE HONORABLE MAYOR AND CITY COUNCIL Dear Members of the Council:

The Undersigned has examined the plans, specifications and locations of the work described herein and is fully informed as to the nature of the work and conditions relating to its performance and understands that the quantities shown are approximate only and are subject to either increase or decrease.

The Undersigned hereby proposes to furnish all the necessary machinery, tools, apparatus and other means of construction, do all the work, furnish all materials except as otherwise specified herein, and, for the unit prices names in the Itemized Bid, to complete the work herein described in strict accordance with the plans therefore and in strict conformity with provisions and supplemental specifications as may be a part of this Proposal. The Undersigned further proposes to do such extra work as may be authorized by the City, prices for which are not included in the Itemized Bid. Compensation shall be made on the basis agreed upon before such extra work is begun.

The Undersigned hereby notes receipt of Addendum No's,
☐ The Undersigned hereby acknowledges the completion of the enclosed Contractor Safety Qualification Statement on page 7 of these documents. (place an "X" in this box)
The Undersigned encloses a certified check or bid bond in the amount of
In submitting this Proposal, it is understood that the City reserves the right to accept or reject any or all Proposals, to waive irregularities or defects in any and all Proposals and may accept other than low bid when deemed in the City's best interest.
FIRM:
BY:
(signature)
ADDRESS:

City of Midland Contractor Safety Qualification Statement

Contract Company:						
Safety Officer:						
Contractor experience modification rate (EMR):			OSHA Recordable Injury Inci	dent Rate (past	year):	
We have received a written copy of and Yes No D		follow the ments:	requirements of the City of M	lidland's "Contra	ctor Safe	ety Progra
We have an active written safety progra	am which v No	vill be prov	vided to City representatives (Comments:	upon request.		
We understand the essential require good faith effort to follow them. We employees:						
	Yes	N/A			Yes	N/A
a. Use of reflective safety vests b. Confined space entry c. Control of hazardous energy d. Elevated work e. Excavations, trenches & shoring f. Personal protective equipment g. Work area protection and traffic control			h. Welding and cutting i. Hazard communication ("rig j. Alcohol and drug use k. Bloodborne pathogens l. Respiratory protection m. Other applicable regulation			
Project-specific concerns of app discussed and documented Important! The City reserves th safety program, training and cer the work being done.	at the po	re-projed reques	ct meeting with City repr t verification, in writing, (resentatives. of the contrac	ctor's c	urrent
Other comments:						
We attest that the above infor substantiated if requested.	mation	is true t	o the best of our know	vledge and c	an be	
substantiated ii requested.			Received by:			
Contract Representative:			Contracting De	ept.:		
Title:	D	ate:	Name:		Date:	
MI Contractor's License No. (if appli	cable):		Original to: Copy to:	Contracting Dep Contractor	artment	

- 7 -

4/05 GP

Contractor Project Safety Plan

To be completed at pre-project meeting along with City contract representative.

Project name: 2015 St. MARYS & VALORIE ST. RECONST.; CONTRACT NO. 2					
Date:					
	*Safety Concerns of t	he Job	(check all that apply)		
1. 🗖	Traffic control*	9. 🗖	Welding and cutting		
2. 🗖	Hazardous energy	10. 🗖	Bloodborne infectious diseases		
3. 🗖	Excessive noise	11. 🗖	Chemical exposures**		
4. 🗖	Hazardous chemicals	12. 🗖	Trenching/excavations		
5. 🗖	Falling objects	13. 🗖	Eye hazards		
6. 🗖	Confined space	14. 🗖	Foot hazards		
7. 🗖	Elevated work	15. 🗖	Hand hazards		
8. 🗖	Respiratory hazards	16. 🗖	Other:		
* Must at	* Must attach traffic control plan				

Safety Concern # (see above)	Control measures (protective equipment, engineering controls, administrative controls, other measures)

^{**} Must have copies of MSDSs for all hazardous chemicals on-site.

CITY OF MIDLAND, MICHIGAN

ADVERTISEMENT

NOTICE TO CONTRACTORS:

Sealed bids on the "2015 ST. MARYS & VALORIE STREET RECONSTRUCTION; CONTRACT NO. 2", will be received in the office of the City Clerk, in the City Hall, 333 West Ellsworth Street, Midland, Michigan 48640 until 2:00 p.m., January 20, 2015, after which time no further bids will be received. All bids will be publicly opened and read at this time and place. Bids will be tabulated and a contract may be awarded at a later City Council meeting.

CONTRACT NO. 2 is for the reconstruction of St. Marys Drive from Valorie Lane to Drake Street and Valorie Lane from St. Marys Drive to Drake Street. Some of the quantities listed in the Itemized Bid are as follows:

9450 S.Yd. Crushing & Shaping Asphalt Pavement

1700 Tons Bituminous Pavement

6520 L.Ft. Remove & Replace Curb & Gutter 17,750 S.Ft. 5" Reinf. Concrete Drive & Ramp

800 S.Ft. 4" Concrete Sidewalk

The Proposal, Contract Forms, Plans and Specifications may be examined and obtained at the office of the Purchasing Agent, City Hall, Midland, Michigan OR at the City of Midland Website at www.cityofmidlandmi.gov on the purchasing page.

A certified check or bid bond for a sum of not less than five percent (5%) of the amount of the Proposal will be required with each bid.

The City reserves the right to accept or reject any or all bids, to waive irregularities or defects, and may accept other than the low bid when deemed in the City's best interest.

Selina Tisdale, City Clerk Midland, Michigan

BID NO. 3677

	CITY OF MIDLA 2015 ST. MARYS & VALORIE		EERING DEPAR		0. 2
	-	ITEMIZE			
				UNIT	
NO.	<u>DESCRIPTION</u>	<u>UNIT</u>	<u>QUANTITY</u>	<u>PRICE</u>	<u>AMOUNT</u>
1	M.H. Casting EJ 1040 A	Each	10		
2	M.H. Casting EJ 1040 AGS	Each	9		
3	C.B. Casting E.J. 7000 M	Each	18		
4	Sidewalk Ramp Warning Plate (24 x 48")	Each	10		
5	8" Catch Basin Lead (SDR-35)	L.Ft.	160		
6	36" Dia. Catch Basin	V.Ft.	10		
7	Regrade Drainage Structure	Each	19		
8	Reconstruct Drainage Structure	V.Ft.	20		
9	Remove Drainage Structure	Each	2		
10	Remove Concrete Curb & Gutter	L.Ft.	6520		
11	Remove Conc. Walks & Drives	S.Yd.	1500		
12	Remove Bituminous Driveway	S.Yd.	35		
13	Remove Existing Pipe	L.Ft.	160		
14	Excavation for Sidewalk Ramps	C.Yd.	60		
15	Sub-Grade Undercut	C.Yd.	50		
16	Saw-Cutting Bit. Pavement	L.Ft.	250		
17	Crushing & Shaping Asphalt	S.Yd.	9450		
18	Aggregate Removal	S.Yd.	9450		
19	Brine Stabilization	Gal.	6330		
20	5" Reinf. Conc. Curb & Gutter	L.Ft.	6520		
21	5" Reinf. Concrete Sidewalk Ramp	S.Ft.	600		
22	5" Reinf. Concrete Drive	S.Ft.	11750		
23	4" Concrete Sidewalk	S.Ft.	800		
24	5" Gravel Driveway	S.Yd.	35		
25	Fine Grading	L.Ft.	3260		
26	Bit. Level Course Mix #3	Ton	850		
	Bit. Top Course Mix #2 - Street	Ton	850		
28	Bit. Top Course Mix #2 - Driveways	Ton	10		
29	4" Outlawn	S.Yd.	6500		
	Hydroseeding	S.Yd.	6500		
31	Traffic Control	L.Sum	1		
32	Dust Control	Gal.	1450		
33	Catch Basin Sedimentation Bags	Each	20		
				TOTAL DID	
				TOTAL BID	

LIST OF SUBCONTRACTORS

NOTE: THIS SHEET MUST CONTAIN ALL SUBCONTRACTORS WHO WILL PERFORM OVER \$5,000 WORTH OF WORK ON THIS CONTRACT. NON-SUBMITTAL OF THIS INFORMATION MAY CONSTITUTE AN INCOMPLETE BID AND MAY BE GROUNDS FOR DISQUALIFICATION.

<u>SUBCONTRACTOR</u>	TYPE OF WORK	VALUE OF WORK
<u>CONTRACTOR</u>		

SPECIAL PROVISIONS page 1 of 4

SCOPE OF WORK:

This project consists of reconstruction and resurfacing of St. Marys Drive from Valorie Lane to Drake Street and Valorie Lane from St. Marys Drive to Drake Street. This project will include removal and replacement of all the curb on the street within the project limits. All curb and driveway replacements shall be completed on one side of the street before beginning removals on the other side of the street. The roadway reconstruction shall consist of removal and replacement of all concrete curb and gutter and drive approaches from the curb to the sidewalk, followed by crushing, mixing and shaping of the existing bituminous pavement courses with the existing aggregate base to a depth of at least eight inches (8") from the top of the existing pavement surface. Following the crushing operation, approximately 3" of aggregate mixture shall be removed and an application of 38% Calcium Chloride solution shall be applied at the rate of 0.50 gallons per square yard. Following brine application, the street shall be crushed again to mix the brine into the aggregate surface to a depth of six inches (6"). The street shall then be graded and compacted and an application of Calcium Chloride shall be applied at a rate of 0.17 gallons per square yard applied to the surface and cured for a sufficient time as determined by the Engineer. Following curing of the surface treatment of Calcium Chloride, the street shall receive 1-1/2" of Bituminous Leveling Course and 1-1/2" of Bituminous Top Course. This work shall also include regrading and replacement of all manhole castings and catch basin castings affected by curb replacement. The existing castings shall be removed prior to crushing the pavement and replaced following placement of the levelling course. Concrete driveways and sidewalk ramps shall be replaced with a 5" reinforced concrete surface and bituminous drives shall be replaced with a 5" aggregate base and 2" of bituminous top course.

PROGRESS SCHEDULE:

The bidder is directed to the provisions of Section 1.03.02 which shall be a prior condition to the execution of the Contract.

Prior to the beginning of work, the successful bidder, along with representatives of the City, Consumers Energy and A.T. & T. shall meet at a mutually agreeable time to discuss coordination of schedules in order that the successful bidder may comply with the requirements of Section 1.03.02 of the General Conditions. The entire project shall be completed on or before June 30, 2015. See "Project Inspection" below for costs of project inspection beyond this completion date.

PROJECT INSPECTION:

The City of Midland will be overseeing and inspecting this project. The City will schedule personnel to complete the inspection services during the Contract progress schedule shown above at 50 hours per week. If the Contractor and/or Sub-Contractors work more than 50 hours per week, inspection services will be charged against the Contractor at a rate of \$90 per hour. All inspection hours required after the completion date shown above, the Contractor will be charged \$60 per hour up to 40 hours in one week and then the rate will be increased to \$90 per hour to cover overtime charges. The amount of the extra inspection charges above the 50 hours per week and any inspection required after the completion date will be deducted from the Contractors payment.

PAYMENT:

The Contractor's attention is directed to Section 1.09.07 for provisions pertaining to progress payments under this Contract.

CATCH BASIN LEAD REPLACEMENT:

The price bid per lineal foot of 8" Catch Basin Lead and Sanitary Lateral shall include excavating to the sewer and removal and saw-cutting (if needed) of existing pipes and all bends and fittings (fernco) required to reconnect the new sewer pipes to the existing pipe, manhole or catch basin and all sand backfill and compaction. The Contractor shall be responsible for maintaining flow in the sewers. Following pipe installation and backfill, the trench areas shall be graded to accept 6" Aggregate Base Course to the level of the existing pavement.

SPECIAL PROVISIONS page 2 of 4

TRAFFIC REQUIREMENTS:

All Streets affected by this Contract shall remain open to local traffic and closed for thru traffic during the completion of this project. All signing and barricades within the project limits shall be the responsibility of the Contractor and shall conform to the requirements for construction signing in the current edition of the Michigan Manual of Uniform Traffic Control Devices. Street closures shall be the responsibility of the Contractor. The Contractor shall submit a traffic control plan at the pre-construction conference for approval by the Engineer. A recommended traffic control plan is included herein. No work shall commence until proper signing and barricading is in place and verified by the Engineer.

The Contractor shall be responsible for furnishing, installing and maintaining all traffic control signs.

5" REINFORCED CONCRETE SIDEWALK RAMPS:

The price bid per square foot of "5" Reinforced Concrete Sidewalk Ramps" shall include the cost of minor excavation to achieve the desired grade and constructing the sidewalk ramps to a depth of 5" with steel 6"x 6" 10 Gauge woven wire mesh reinforcement.

All ramps shall receive Armor-Tile Tactile Systems Vitrified Polymer Composite replaceable cast in place detectable warning plates as shown on the detail sheet contained herein. The warning plates shall be 24" x 48" Colonial Red in color. These shall be installed as per the manufacturers recommendations. These shall be paid for at the unit price bid per each 24" x 48" "Sidewalk Ramp Warning Plate".

CRUSHING & SHAPING ASPHALT PAVEMENT:

The bid item of "Crushing & Shaping Asphalt Pavement" shall consist of crushing, mixing and shaping of the existing bituminous pavement courses with the existing aggregate base to a depth of at least eight inches (8") in depth from the top of the existing pavement surface. This shall also include crushing again following sewer repairs and concrete flat work. Following the second crushing, the brine stabilization shall be added and crushed and mixed again. Crushing, mixing and shaping shall be completed in accordance with Michigan Department of Transportation (M.D.O.T.) Standard Specifications, Section 305, "Bituminous Base Crushing and Shaping". Equipment used for crushing shall be in conformance with M.D.O.T. Standard Specification Section 305.

BRINE STABILIZATION:

The price bid per gallon of "Brine Stabilization" shall consist of the application of a 38% Calcium Chloride solution at a rate of 0.50 gallons per square yard following aggregate removal. The aggregate and brine shall then be mixed using the same device used for the crushing and shaping operation. Following final grading and compaction, a 38% Calcium Chloride solution shall be placed over the entire street area at a rate of 0.17 gallons per square yard. The Contractor shall work closely with the Engineer so as to determine that proper curing of the brine solution has occurred prior to placement of asphalt leveling course.

BACKFILL:

Clean sand shall be used for backfill in all Water Main, Sanitary Sewer, Storm Sewer, Catch Basin Lead and Manhole trenches. The price for sand backfill shall be considered incidental to the unit price bid per lineal foot of pipe and manhole or catch basin installation.

DISPOSAL OF MATERIALS:

All excess excavation and pavement material that will not be used on this project, shall be disposed of by the Contractor. Disposal, including any applicable landfill use fees, of all removal items and excess excavation shall be the Contractor's responsibility.

BITUMINOUS PAVEMENT SPECIFICATIONS:

Marshall Stability design method, but the Contractor should note that the specifications do not necessarily copy those of MDOT and that the Master Design Mix (Table 1) defines the mix specified on the plans or on the Itemized Bid sheet. The provisions for penalties exist for bituminous mixes exceeding the tolerance limits permitted by the specifications.

SPECIAL PROVISIONS page 3 of 4

TEMPORARY ROADWAYS AND DRIVEWAYS:

The Contractor shall maintain a temporary roadway and driveway surfaces to homes affected by this project. This shall be accomplished by the placement of aggregate material sufficient to carry traffic on a temporary basis. This will cause minimal disruption for residents during construction. The Contractor is required to maintain the temporary roadway and driveways in a serviceable condition until the final road and driveway reconstruction is complete. The cost for this work is incidental to this project.

DRAINAGE STRUCTURE REGRADES:

Existing castings shall be salvaged and re-used on this project. The bid item for each "Regrade Drainage Structure" shall include adjusting the top of the masonry structure to the finished grade, with casting installed. The method for regrading shall include the placement of precast reinforced concrete adjusting rings in accord with ASTM C-478. Brick will not be allowed for regrades. The casting and all adjusting rings and 6" of the original structure shall be covered with a mastic patching and surfacing compound material at a thickness of 1/8TH inch. The mastic material shall be Tremco Inc. TREM proof 250 GC-R or approved equal. Prior to the mastic setting-up, a minimum of an 18" wide piece of external pipe joint material meeting Mirafi 140 shall be wrapped around the circumference of the structure and shall overlap at least 6" installed around the top of the structure and casting to seal the joint from water entering the sewer system. The structure shall be cleaned thoroughly prior to placing the mastic material. All Manhole castings and all Catch Basin Castings affected by curb replacement shall be removed and replaced with new castings. The cost for each "Regrade Drainage Structure" shall also include replacement of 6" Aggregate Base Course (22A crushed limestone) and 2" of Bituminous Leveling Course to the level of the bottom of the new wearing course. Regrades shall not be paid for new structures.

RESTORATION:

All landscaping and outlawns shall be restored to a condition equal to or better than prior to construction. Any areas disturbed by the Contractor's operations shall be backfilled, covered with 4" of topsoil, neatly graded, prepared as described in Section 6.53.03 (Outlawn) of these Specifications, and hydroseeded. A GRADE INSPECTION SHALL BE PERFORMED AND APPROVED BY THE FIELD ENGINEER PRIOR TO PLACEMENT OF ANY HYDROSEED.

CONCRETE CURB & GUTTER INSTALLATION:

The price bid per lineal foot of "Remove Concrete Curb & Gutter" shall include the cost of removing any bituminous pavement next to the curb required for the installation of forms for the construction of the new curbs and placement of a temporary aggregate base to allow access to driveways.

DUST CONTROL:

Dust control shall be accomplished by the placement of 38% calcium chloride solution on the roadway at a rate to be determined by the Engineer. Clean water shall be used for dust control on all lawn areas.

SUBGRADE UNDERCUT:

The price bid per cubic yard of Sub-grade Undercut Excavation shall include excavation of unsuitable roadway sub-base material as determined by the Engineer and replacement with Class II sand and replacement of the aggregate base with crushed pavement material.

road and driveway reconstruction is complete. The cost for this work is incidental to this project.

SAW CUTTING PAVEMENT:

The price bid per lineal foot of "Saw-Cut Pavement" shall include the full depth saw cutting of the existing roadway pavement. All saw cutting of concrete curb, sidewalks & driveways shall be included in the unit price bid for removal of those items.

BUTT JOINTS FOR BITUMINOUS PAVING:

Butt joints shall be saw cut into the existing asphalt pavement to provide a neat ending joint for the new pavement and to eliminate the need for feathering the new asphalt surface. The cost of making the butt joints shall be paid for at the unit price bid for saw-cutting pavement.

SPECIAL PROVISIONS page 4 of 4

FIRST AID TRAINING:

The Contractor shall have a person on site at all times that has a valid certificate in first aid training. The certificate shall be from the American Red Cross or equivalent training program. A first aid kit shall be provided at the job site and shall be inspected weekly to assure that used items are replaced. This is a requirement of MIOSHA Rule 132.

SOIL EROSION AND SEDIMENTATION CONTROL:

The Contractor shall conduct his operations so as to minimize soil erosion and sedimentation into surface water courses and storm sewers. The Contractor shall be responsible for installing all of the soil erosion control measures shown on the plans and in accordance with the details shown herein and on the plans. The Contractor is responsible for all SESC within the work influence area and adjacent to and/or downstream from any work zone track out. The Soil Erosion and Sedimentation Permit has been obtained by the City of Midland Engineering Department for this project. The Contractor shall install sedimentation bags in all catch basins within the project work area. The lump sum price bid for each "catch basin sedimentation bags" shall include the furnishing, installation and maintenance of sediment trapping bags installed inside the catch basins at the locations shown on the plans and shall be "Siltsack" or approved equal. All aggregate, sand and soil stockpiles created by the Contractor for the completion of this project shall be surrounded with silt fence to eliminate the possibility of erosion and the cost thereof shall be the responsibility of the Contractor. Unit prices for soil erosion control measures shall also include the removal of all SESC measures following construction and when final turf has been established.

CONFINED SPACE ENTRY CONTRACTOR OBLIGATIONS:

The City of Midland is in compliance with Occupational Safety and Health Standard, Part 1910, regarding permit-required confined space entry. A copy of the City of Midland Master Plan for Permit-Required Confined Space Entry can be obtained from the City Personnel Department in City Hall, 333 W. Ellsworth Street.

All contractors or sub-contractors conducting permit-required confined space entry shall have a written permit-required program meeting requirements of 29 CFR 1910.46 and shall provide written proof of that program with the bid documents. Contractors shall comply with the requirements of Part 1910 and all other State and Federal laws concerning confined space entry at all times.

SAFETY:

The Contractor shall be responsible for complying with all current laws and regulations pertaining to Manhole (Confined Space) Entry, Trenching & Shoring, Workzone Traffic Control, Personal Protective Clothing, etc. as outlined in the Contractor Safety Qualification Statement. Prior to commencement of work, the Contractor shall provide copies of their safety policy and manual and those for all subcontractors for information and reference. Indicate name and position of company safety officer and dates of regular safety meetings.

MICHIGAN RIGHT TO KNOW LAW AMENDMENT TO ACT 154 (86 p.a. 80):

Hazardous Materials:

It is the responsibility of the Contractor to provide the Purchasing Agent or applicable department head with the following information:

- Hazardous chemicals to which City employees may be exposed to while on the job site.
 - Steps the Contractor has taken to lessen the risks.
 - Measures that City employees may take to lessen the risks.
 - Procedures to follow if City employees are exposed.

The Contractor must provide an inventory list of all hazardous materials used on the job site during the term of the contract. This list must be attached to the contract/bid proposal document.

This list shall include, but is not limited to:

Fuels, lubricants, pipe, pipe mastics, pipe lubricants, cements, and asphalt materials.

The successful bidder shall provide the City Purchasing Agent or applicable department head with Material Safety Data Sheets (MSDS's) for all hazardous materials to be used on the job site prior to the start of work.

HAZARDOUS MATERIALS INVENTORY

	ARDOUS MATERIALS INVEN	
Product	Company	Address



 $Engineering\ Department\ ^{\sim}\ City\ Hall\ ^{\sim}\ 333\ West\ Ellsworth\ Street\ ^{\sim}\ Midland,\ Michigan\ 48640-5132\ ^{\sim}\ 989-837-3348\ ^{\sim}\ www.midland-mi.org$

		2015 ST.MARYS & VALORIE STREET RECONST.	2
Date		Contract Name	Contract #
Date		Contract Name	Contract #
			_
	Check	Soil Conditions	
		Compaction	
		Depth	
		Grading	
		Quality/Condition	
		Weeds/Debris]
Contractor		has met the required Soil Conditions, as indicated	d above, and is
uthorized to place Hydro S	eed on		
		Location	
Contractor's authorized repre	esentative	s's signature Inspector's signa	iture